PRINTBRISK

ARTWORK TEMPLATE

Edgefit Replacement SEG Fabric Graphics

seg fabric pop up 4x3 double sided

01 Match your order

Check the exact size, orientation and configuration before designing. This pack is for the product named above.

02 Use the original-size guide pages

The following guide pages retain their production dimensions and scale. Follow the scale printed on each guide. Do not fit them to A4 or enlarge them automatically.

03 Extend backgrounds into bleed

Follow the bleed, cut, finishing and safe-area lines on the guide. Keep logos and important wording inside the safe area. Hardware pockets and hidden areas are not visible print space.

04 Export your artwork only

Remove guide lines and instructions from your print file. Supply a print-ready PDF with embedded images and outlined fonts. Screen previews are not colour proofs.

05 Need artwork produced?

Add the design and artwork service for £45 + VAT (£54 including VAT) per product design. We will email a proof for approval before printing.


SEG FABRIC POP-UP (4×3)

DOUBLE-SIDED

Size

This template is 20% scale of full size, and must not be re-sized or scaled.

Top-Down View



Shape

Bleed line
Artwork must extend to this line. The area in between this line and the safe area line must only be used as a quiet area.

Finished line
Approximate perimeter of the visible graphic area, after the graphic has been finished and fitted to the frame.

Safe area line
Important content (text, logos etc.) must be kept within this line.

Layers

Design. Must be used to create and supply your design.

Guide. Must not contain any of your design elements. Must be deleted before saving your print-ready file.

Artwork Requirements

Artwork must be supplied:

- At the exact size of this template
- With all fonts outlined
- With all images embedded
- With all design elements on the Design layer
- With background/quiet content all the way to the bleed line(s)
- With all important content inside the safe area(s)
- With none of the template guide lines included or flattened
- With all template elements and text removed
- With no crop marks, bleed marks, colour bars or other registration marks present
- As either PDF (preferred), AI or EPS format
- With artwork for all sides included
- With exported files checked (e.g. in Adobe Acrobat/Reader) that all design elements are included

For a full list of artwork requirements, please refer to our website.

Considerations

While we make every effort to finish these graphics as accurately and consistently as possible, due to the nature of printing, cutting and finishing fabrics, some material movement and minor imperfections in alignment can be introduced and cannot always be avoided. For this reason, important content, such as logos and text, should not escape the safe areas, and we highly recommend not attempting to span continuous or detailed shapes between sides.

Our thread colours are black or white. Our sewists will choose the most appropriate colour to complement your graphic. The only visible stitching when fitted is at the top and bottom of the left and right sides.

Currently, the dye-sublimation process does not allow for the use of Pantone colours. Any Pantone colours must either be converted to (or replaced with) CMYK colours before supplying your print-ready file.

LEFT

FRONT

Please refer to the instructions on the first page.

All artwork elements must be supplied on the Design layer. The Guide layer must be deleted before saving your print-ready file.

This text must be deleted.

RIGHT

REAR